

HENRY COMPANY CANADA INC.

10 St-Pierre, Lachine, Quebec H8R 1N7
Tel.:(514) 364-5224 Fax:(514)364-7270

EMERGENCY TEL. NO.: (514) 364-5224

MATERIAL SAFETY DATA SHEET

WHMIS: B-3, D-2B

I - PRODUCT INFORMATION

PRODUCT NAME	Bakor Air-Bloc 06 Regular / Air-Bloc 06 Spray
PRODUCT TYPE	Rubberized Asphalt/Solvent Blend
PRODUCT USE	Air barrier membrane

II - HAZARDOUS INGREDIENTS

INGREDIENTS	%	CAS #	EXPOSURE LIMITS	LD50/LC50(SPECIES & ROUTE)
Stoddard Solvent	10-30	8052-41-3	100 ppm, TLV	LD50(oral-rat) > 5000 mg/kg LC50(inhal.-rat) > 5g/m3
Naphtha solvent, light aromatic	10-30	64742-95-6	50 ppm (245 mg/m3) 8 hr. work day	LD50(oral-rat) > 4700 mg/kg LC50(inhal.-rat) > 1400 ppm
Silica (amorphous)	1-5	112945-52-5	10 mg/m3 (ACGIH)	LD50(oral-rat) > 10 000 mg/kg
Heavy paraffinic distillate	1-5	64742-04-7	5 mg/m3	Not applicable

III - PHYSICAL DATA

PHYSICAL <input type="checkbox"/> GAS STATE <input checked="" type="checkbox"/> LIQUID <input type="checkbox"/> SOLID	ODOUR & APPEARANCE Black liquid with aromatic solvent odour.	ODOUR THRESHOLD (ppm) Not available	
VOLATILE (VOL.) VOC 35 - 39% < 375 g/L	VAPOUR PRESSURE (mm Hg) 5 - 15 at 38°C	VAPOUR DENSITY (AIR = 1) 3.9 - 4.5	EVAPORATION RATE (BuAc=1) 0.10 - 0.20
BOILING POINT (°C) 140 - 200°C	FREEZING POINT (°C) Not applicable	SPEC. GRAVITY (WATER - 1) 0.91	DENSITY (g / ml) 0.91
SOLUBILITY (IN WATER) Insoluble	COEF. OF WATER/OIL DIST. Not available	pH Not applicable	

IV - FIRE & EXPLOSION HAZARD

FLAMMABILITY <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	CONDITIONS OF FLAMMABILITY Avoid excessive heat and open flames.	
FLASH POINT (°C): 43°C METHOD: PMCC	FLAMMABLE LIMITS (% VOLUME) LOWER: 1.0 UPPER: 7.0	AUTO-IGNITION TEMP. (°C) 245°C for solvent
TDG FLAMMABILITY CLASS Class 3, PG III	SENSITIVITY TO MECHANICAL IMPACT None	SENSITIVITY TO STATIC DISCHARGE If product above flash point.
HAZARDOUS COMBUSTION PRODUCTS	On burning some SO2 and traces of CO. Main combustion products are H2O, CO2 and C (as heavy smoke).	
MEANS OF EXTINCTION	Foam , carbon dioxide, dry chemicals, water spray (for small fires).	
SPEC. FIRE FIGHTING PROCEDURES	Contain spill. Cover with extinguishing agents. Use water spray to cool fire-exposed containers Self-contained equipment and full protective clothing when fumes or smoke are present.	

V - PREPARATION OF M.S.D.S.

PREPARED BY: WHMIS Group	PHONE NUMBER (514) 364-5224	DATE May 2006
-----------------------------	--------------------------------	------------------

VI - REACTIVITY DATA		Bakor Air-Bloc 06 Regular, ...
CHEMICAL [X] YES STABILITY [] NO	CONDITIONS TO AVOID: Sources of ignition, excessive heat approaching flash point.	
INCOMPATIBILITY (SUBSTANCE TO AVOID)	Strong oxidizing agents may ignite the product.	
CONDITIONS OF REACTIVITY	None.	
HAZARDOUS DECOMPOSITION PRODUCTS	Will not decompose under normal conditions of handling and warehousing.	

VII - TOXICOLOGICAL PROPERTIES			
THRESHOLD LIMIT VALUE	100 ppm	LC50/LD50 (estimated)	LD50(oral-rat) > 4700 mg/kg LC50(inhal.-rat) > 1400 ppm
ROUTE OF ENTRY	<input checked="" type="checkbox"/> SKIN CONTACT	<input type="checkbox"/> SKIN ABS.	<input checked="" type="checkbox"/> EYES <input checked="" type="checkbox"/> INGESTION <input checked="" type="checkbox"/> INHALATION
EFFECTS OF ACUTE EXPOSURE	Inhalation of high concentrations of vapours can cause headache, dizziness, nausea and unconsciousness. Can cause gastro-intestinal irritation, nausea, vomiting, diarrhea if ingested in large quantity.		
EFFECTS OF CHRONIC EXPOSURE	Prolonged or repeated skin contact may cause severe skin problems as lesions of dermatitis. Vapours may also irritate eyes, nose and throat.		
IRRITANCY	Skin irritancy after prolonged or repeated contacts.	SENSITIZATION	Not available
		SYNERGISTIC MATERIALS	Not available
<input type="checkbox"/> CARCINOGENICITY	<input type="checkbox"/> REPRODUCTIVE EFFECTS	<input type="checkbox"/> TERATOGENICITY	<input type="checkbox"/> MUTAGENICITY
Not believed to cause any of these effects.			

VIII - FIRST AID MEASURES	
SKIN	Thoroughly wash exposed areas with waterless cleaner or soap and water.
EYES	Flush eyes thoroughly with plenty of lukewarm water. Get medical attention immediately.
INHALATION	Remove victim to fresh air. Administer artificial respiration if breathing has stopped, administer oxygen. Consult a physician immediately.
INGESTION	DO NOT INDUCE VOMITING. If vomiting occurs, take care to prevent aspiration into lungs. Force fluids, activated charcoal tablets. Obtain medical attention immediately.

IX - PREVENTIVE MEASURES	
PERSONAL PROTECTIVE EQUIPMENT	EYES: Goggles if applied by spray.
	GLOVES: Suggested (neoprene, nitrile).
	CLOTHING: Oil resistant apron and/or clothing if direct contact is likely.
	RESPIRATORY: Use approved, organic vapour mask in confined areas or if applied by spray.
ENGINEERING CONTROLS (VENTILATION, ETC.)	Ventilation required in confined areas. Local exhaust, if necessary, to maintain TLV.
LEAK AND SPILL PROCEDURE	Avoid breathing fumes and contact with skin and eyes. Avoid sources of ignition. Contain with absorbent solids such as sand, earth, etc.
WASTE DISPOSAL	Bury in approved landfill or burn in approved incinerator as per state, federal and provincial regulations.
HANDLING PROCEDURES	Normal
STORAGE REQUIREMENTS	Store in cool, well ventilated areas. Keep away from ignition sources.
SHIPPING INFORMATION	TDG regulations not applicable for shipments on a road vehicle, a railway vehicle or a ship on a domestic voyage if shipped in means of containment of 450L or less. Tars, liquid; UN1999; Class3, Packing Group III.

While Henry Company Canada Inc. believes that the data contained herein are factual & opinion expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as warranty or representation for which Henry Company Canada Inc. assumes legal responsibility. These are offered solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with federal, provincial or municipal laws and regulations.