

# PITTSBURGH CORNING FOAMGLAS®

## INSULATION ACCESSORIES

800 Presque Isle Drive  
Pittsburgh, Pennsylvania 15239-2799  
Tel: 724/327-6100 • 800/359-8433  
Fax: 724/327-5890  
www.foamglasinsulation.com

### DESCRIPTION:

PITTSEAL® 727 sealant is a specially formulated styrene-butadiene rubber sealant used for sealing joints in FOAMGLAS® insulation systems, and to seal protrusions and metal jacket laps. It is the preferred sealant for chilled water applications. PITTSEAL® 727 sealant is compatible with a wide variety of coatings.

### USES:

- Joint sealant in FOAMGLAS® insulation pipe covering and between insulation blocks in chilled water applications.
- Bedding compound behind FOAMGLAS® insulation.
- Anti-Abrasive cushion in vibrating systems, usually in conjunction with PC® Anti-Abrasive 2A coating.
- Seal protrusions and metal jacket laps.

### \*TYPICAL PROPERTIES:

Color:	White
Wt/gallon (lbs.):	11.5 to 12.0 (1.37 to 1.43 kg/liter)
Solids, wt %:	72 to 75
Solvent:	Mineral Spirits
Flash Point (PMCC), °F:	105 (40.5°C)
**Flame Spread index, ASTM E84:	5
**Smoke Development index	0
Application Temperature (°F):	0 to 100 (-17.7°C to 38°C)
***Service Temperature (°F):	-70 to 180 (-56.6°C to 82°C)
Permeability, ASTM E96:	.003 perm in (.005 perm cm)
Coverage:	12.8 ft <sup>2</sup> /gal = 1/8" film (smooth (.31 m <sup>2</sup> /l = 3 mm) surface) 25.6 ft <sup>2</sup> /gal = 1/16" film 62 m <sup>2</sup> /l = 1.5 mm) 77 ft/gal = 2" x 1/8" joint (6.2 m/l = 5 cm X 3 mm)

\*Typical properties at time of printing, subject to change

\*\*Tested as joint sealant with FOAMGLAS® insulation under application conditions.

\*\*\*At sealant location.

## PITTSEAL® 727 SEALANT PRODUCT DATA SHEET

**IMPORTANT: MATERIAL SAFETY DATA SHEETS ARE AVAILABLE AND SHOULD BE READ BEFORE USING THIS PRODUCT.**

### APPLICATION:

**DO NOT THIN.** Apply with trowel, knife or caulking gun. All surfaces should be dry and free of dust, loose scale, oil, grease and frost. Apply sufficient material to both surfaces and press surfaces together firmly to obtain a complete seal. Joints less than or equal to 1/8" (3mm) are desirable. **Do not use this or any other sealant to fill large voids from poor fitting.** Blocks or joints should be rubbed to obtain good fit before application of sealant. If a coating is to be applied, cut off any squeezed-out sealant flush with surface. When sealing laps of metal jacketing, maintain a 1/16" (1.5mm) minimum thickness. Allow to cure one week before placing in hot service.

PITTSEAL® 727 sealant works easily over the suggested application range. To facilitate application at low temperature, keep containers in a heated location or loosen lid and warm by indirect heat. **DO NOT HEAT** containers with flame or direct heat.

### CLEAN UP AND DISPOSAL:

Tools should be cleaned with mineral spirits. See Material Safety Data Sheet for proper disposal.

### LIMITATIONS:

**DO NOT** use in applications where solvent odor could affect food taste or flavor. Solvent may attack some organic foams.

### PACKAGING:

- 10 fl. oz. cartridges (12/case)
- 2, 5, and 52 gallon containers

### SHIPPING INFORMATION:

Domestic land: Flammable Liquid nos. UN 1993  
ICAO, IATA, UN: Flammable liquid, UN 1993. Class 3.3  
IMCO:PACKING Group III, same as UN

### CAUTION:

**This material is intended to be used only with FOAMGLAS® insulation and in conformity with Pittsburgh Corning's standard instructions. Be sure you have read and understand all instructions and Material Safety Data Sheets before using.**

<b>INGREDIENTS:</b>	<b>CAS #</b>
Styrene-Butadiene rubber	9003-55-8
Styrene-Butadiene rubber	26471-45-4
Hydrocarbon resin	68131-48-6
Calcium Carbonate	1317-65-3
Mineral spirits	64742-48-9

**IRRITANT:**

IARC Cancer Review (SBR) Group 3 Human Evidence Inadequate

**Repeated or prolonged contact may irritate skin, eyes and respiratory system. Wear gloves. When working overhead wear goggles. Use with adequate ventilation.**

**HARMFUL OR FATAL IF SWALLOWED**

**COMBUSTIBLE MIXTURE:**

Contains up to 28% by wt. mineral spirits (CAS 64742-48-9. Keep away from open flame and ignition sources. Keep container closed when not in use. Store in areas for combustibles.

**FIRE HAZARD CLASSIFICATION:**

Health: 1 Fire: 2 Reactivity: 0

**KEEP OUT OF REACH OF CHILDREN**

This material is designed for application only for professional, trained personnel using proper equipment and is not intended for sale to the general public

The information contained herein is accurate and reliable to the best of our knowledge. But, because Pittsburgh Corning Corporation has no control over installation workmanship, accessory materials or conditions of application, NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, IS MADE as to the performance of an installation containing Pittsburgh Corning products. In no event shall Pittsburgh Corning be liable for any damages arising because of product failure, whether incidental, special, consequential or punitive, regardless of the theory of liability upon which any such damages are claimed. Pittsburgh Corning Corporation provides written warranties for many of its products, and such warranties take precedence over the statements contained herein.

**FOAMGLAS®, PC® and PITTSEAL® are registered trademarks of Pittsburgh Corning Corporation**

PITTSEAL® 727 SEALANT  
FI-255 5/03