

## OFI-25 1.5 lb Semi-rigid Fibre Glass Board

### ► Specification Data

#### Description

OFI-25 is a semi-rigid thermo-set resin-bonded glass fibre insulation. OFI-25 is soft and easy to cut with a knife. It conforms easily to irregular surfaces. OFI-25 is clean, resilient, and non-toxic. It will not shrink or settle (from exposure, vibration, temperature or humidity), stain or corrode, rot or sustain fungi or vermin.

#### Application

OFI-25 is suited for application on heated and cooled industrial and commercial equipment, between steel studs, as well as for wall panels and roof cavities in pre-engineered metal buildings.

#### Surface Burning Characteristics ULC Listed (CAN/ULC-S102) UL Listed

Flame Spread .....	15
Smoke Developed.....	10

#### Dimensions

Width	610 mm (24")	813 mm (32")
Length	1219 mm (48")	
Available Thicknesses	25-127 mm (1"-5")	

#### Specifications Compliance

<b>CAN/CGSB</b>
51.11.92 TYPE 2 CLASS 2

For non-standard sizes, contact your nearest distributor.

### ► Performance Data

#### Properties

<b>Density</b>	25.63 kg/cu.m (1.5 lb/cu.ft)
<b>Thermal Resistance</b>	rsi = .73/25.4 mm r = 4.1/in
<b>Limits</b>	not to be used on systems working at temperatures higher than 232°C (450°F)
<b>Non combustible</b>	CAN/ULC S114-M80
<b>Moisture Absorption (%/vol)</b>	0.01 (CGSB 51-GP-11M requirement: 1.0% maximum)

Published product property characteristic values are nominal and subject to normal manufacturing tolerances.