

## ARMAFLEX 520 BLV Adhesive - Black, Low VOC Adhesive

- » Formulated for Armaflex Insulations
- » Hexane-free, toluene-free contact adhesive
- » Developed to meet South Coast AQMD
- » Proven: no gapping, no tape needed

### Description

Armaflex® 520 BLV Adhesive is a black, low VOC air-drying contact adhesive that is excellent for joining seams and butt joints of Armaflex Pipe and Sheet Insulations for line temperatures up to 250°F (120°C). No additional tape wrap needed to prevent gapping and moisture infiltration. The adhesive may also be used to apply Armaflex Sheet Insulation to flat or curved metal surfaces that will operate at temperatures up to 180°F (82°C).

- Developed to meet South Coast Air Quality Management District (SCAQMD) Rule 1168.
- Dried film also meets 25/50 flame spread index and smoke developed index requirements of codes and specifications when tested by ASTM E 84 Method.

### Uses

520 BLV Adhesive will make a resilient and heat-resistant bond with many materials where the use of a toluene-free, hexane free, low VOC, solvent-base rubber contact adhesive is suitable and desirable. Armaflex 520 BLV was developed to meet requirements for reduced emissions of Volatile Organic Compounds. Its black color helps achieve a neater, cleaner finished installation.

It will make a strong resilient bond for sealing laminated aluminum foil and kraft paper vapor-retarder jackets.

#### Date of Release:

All data is valid for the application of our products in USA and Canada and Mexico.

Armacell provides this information as a technical service. To the extent the information is derived from sources other than Armacell, Armacell is substantially, if not wholly, relying upon the other source(s) to provide accurate information. Information provided as a result of Armacell's own technical analysis and testing is accurate to the extent of our knowledge and ability, as of date of printing, using effective standardized methods and procedures. Each user of these products, or information, should perform their own tests to determine the safety, fitness and suitability of the products, or combination of products, for any foreseeable purposes, applications and uses by the user and by any third party to which the user may convey the products. Since Armacell cannot control the end use of this product, Armacell does not guarantee that the user will obtain the same results as published in this document. The data and information are provided as a technical service and are subject to change without notice.

Armacell LLC · 7600 Oakwood Street Ext. · Mebane, NC 27302 · tel 919 304-3846 · fax 919 304-3720 · email: info.us@armacell.com · website: www.armacell.com

© Armacell LLC



#### Related information

- Physical Properties
- Application Instructions
- Material Safety Data Sheet
- Installation Guide
- Data Sheet (color)
- Submittal Sheet (b&w)